

ET and MPH based requirements guide

	Licence			
Street Registered cars slower than 11.00 (1/4 mile) / 7.00 (1/8 mile) fitted with Airbags and Four Wheel Disc Brakes		Divisional Day Licence	"Divisional Drag Racing Licence (DDL)" on page 57	
Other Cars Faster than 12.00 (1/4) 7.70 (1/8)		Superstreet licence required for cars faster than 12.00 (1/4 mile) / 8.30 (1/8 mile) but slower than 11.00 (1/4 mile) / 7.00 (1/8 mile)	"Super Street Licence (SSL)" on page 58	
Cars Faster than 11.00 (1/4) 7.00 (1/8)	ICENCE	Unlimited Licence with medical approval required for all cars faster than 11.00 (1/4 mile) / 7.00 (1/8mile)	"Unlimited Licence (UDL)" on page 58	
Motorcycles Slower than 10.00 (1/4) 6.40 (1/8)	TI	Superstreet or Divisional Day Licence for motorcycles slower than 9.50 (1/4 mile) / 6.05 (1/8 mile)	"Super Street Licence (SSL)" on page 58	
Unmodified factory built Motorcycles Slower than 9.50 (1/4) 6.05 (1/8)		Superstreet or Divisional Day Licence for unmodified factory built motorcycles slower than 9.50 (1/4 mile) / 6.05 (1/8 mile)	"Super Street Licence (SSL)" on page 58	
Motorcycles Faster than 10.00 (1/4) 6.40 (1/8)		Unlimited Licence with medical approval is required for motorcycles faster than 10.00 (1/4 mile) / 6.40 (1/8 mile)	"Unlimited Licence (UDL)" on page 58	

		Helmets	
Closed cars Slower than 9.00 (1/4) 5.70 (1/8)		AS/NZS 1698:2006, Snell SA/SAH or M series (2005/2010) or SFI 31.1 / 41.1	
Closed cars Faster than 9.00 (1/4) 5.70 (1/8)		Snell SA/SAH or M series (2005/2010) or SFI 31.1 / 41.1	
Open cars Faster than 10.00 (1/4) 6.40 (1/8)		Snell SA/SAH or M series (2005/2010) or SFI 31.1 / 41.1	
Motorcycles Slower than 10.00 (1/4) 6.40 (1/8)	Helmets	AS/NZS 1698:2006, Snell SA/SAH or M series (2005/2010) or SFI 31.1 / 41.1 FULL FACE HELMET MANDATORY	"Helmets" on page 243
Unmodified Factory built Motorcycles Slower than 9.50 (1/4) 6.05 (1/8)	Ι Ι	AS/NZS 1698:2006, Snell SA/SAH or M series (2005/2010) or SFI 31.1 / 41.1 FULL FACE HELMET MANDATORY	
Motorcycles Faster than 10.00 (1/4) 6.40 (1/8)		Snell SA/SAH or M series (2005/2010) or SFI 31.1 / 41.1 FULL FACE HELMET MANDATORY	
Group 1 Motorcycles		Snell SA/SAH or M series (2005/2010) or SFI 31.1 / 41.1 FULL FACE HELMET MANDATORY	



		 Harnesses	
Slower than 12.00 (1/4) 7.70 (1/8)		3pt OEM Lap Sash Sedans slower than 12.00 (1/4 mile) 7.70 (1/8 mile)	
Faster than 12.00 (1/4) 7.70 (1/8)		4 Point Sedans quicker than 12.00 (1/4 mile) / 7.70 (1/8 mile)	
Slower than 11.00 (1/4) 7.00 (1/8) fitted with 4 wheel disc brakes and airbags	Seat Belts / Harnesses	3pt OEM Lap Sash minimum Sedans slower than 11.00 (1/4 mile) 7.00 (1/8 mile) if vehicle is fitted with 4 wheel disc brakes and factory airbags	"Seat Belts / Harnesses" on page
Sedans Faster than 130 mph	Belts,	5 Point with crotch strap- Sedans faster than 130mph	247
Modifieds Slower than 150 mph	Seat	5 Point with crotch strap - Modifieds slower than 150mph	
Modifieds Faster than 150 mph		5 Pont Centre-locking - Modifieds faster than 150mph	
Faster than 200 mph		5 Pont Centre-locking - All cars quicker than 200mph	
ALL	1	Lap Belts Prohibited - ALL	

		Clothing	
Sedans Slower than 11.00 (1/4) 7.00 (1/8)		Long Sleeve upper, Full Length pants, shoes and socks as minimum - Sedans slower than 11.00 (1/4 mile) / 7.00 (1/8 mile)	
Naturally Aspirated Sedans Faster than 11.00 (1/4) 7.00 (1/8)		Suit SFI 3.2A/5, fire resistant gloves, shoes and socks. Neck collar required if quicker than 7.50 (1/4 mile) / 4.90 (1/8 mile)	
Others Faster than 11.00 (1/4) 7.00 (1/8) - Supercharged Sedans, Competition or Modified and enclosed composite body cars slower than 9.00 (1/4 mile) / 5.70 (1/8 mile)	Clothing	Suit SFI 3.2A/5, fire resistant gloves, shoes and socks. Neck collar in cars quicker than 7.50 (1/4 mile) / 4.90 (1/8 mile)	"Protective Clothing" on page 245
5.70 (1/6 mile)	AUS	STRALIAN NATIONAL DRAG RACING ASSOCIATION UD	

		Clothing	
		Clothing	
- Supercharged Sedans, Competition or Modified and enclosed composite body cars Faster than 11.00 (1/4) 7.00 (1/8)	ρυ	Suit SFI 3.2A/5, fire resistant gloves, boots, socks and underwear, Neck collar in cars quicker than 7.50 (1/4 mile) / 4.90 (1/8 mile)	"Drotostivo Clothing"
Faster than 11.00 (1/4) 7.00 (1/8) - Top Alcohol Dragster & Altered, Supercharged Altered Production, Gas, and rear engined Top Fuel	Clothing	Suit SFI 3.2A/15, SFI 3.3/15 fire resistant gloves, boots. Socks, underwear, Balaclava and Neck collar	"Protective Clothing" on page 245
Faster than 9.00 (1/4 mile) / 5.70 (1/8 mile) -Top Doorslammer, Funny Car, and enclosed composite body cars		Suit SFI 3.2A/20, fire resistant gloves, boots, socks and underwear, Balaclava and Neck collar	
Motorcycles Slower than 10.00(1/4) 6.40 (1/8)	Clothing	Jacket, Full Length pants, gloves, shoes and socks as minimum - Motorcycles slower than 10.00 (1/4 mile) / 6.40 (1/8 mile)	"Protective Clothing" on page 245
Unmodified Factory built Motorcycles Slower than 9.50(1/4) 6.05 (1/8)		Jacket, Full Length pants, gloves, shoes and socks as minimum - Motorcycles slower than 9.50 (1/4 mile) / 6.05 (1/8 mile)	On page 243
Motorcycles Faster than 10.00 (1/4) 6.40 (1/8)		Full leathers or similar, boots 275mm and gloves as minimum - Motorcycles quicker than 10.00 (1/4 mile) / 6.40 (1/8 mile)	



	Body			
Cars Faster than 11.00 (1/4) 7.00 (1/8)		Required for all cars faster than 11.00 (1/4 mile) / 7.00 (1/8 mile)		
Unmodified Factory built Motorcycles Slower than 9.50 (1/4) 6.05 (1/8)	Tech	Not Required	"Technical Inspections" on page 237	
Motorcycles Faster than 10.00 (1/4) 6.40 (1/8)		Required for all motorcycles faster than 10.00 (1/4 mile) / 6.40 (1/8 mile)		

Tyres			
ALL vehicles		Use of speed limited or space saver tyres is prohibited	
All vehicles faster than 12.50 (1/4) 8.00 (1/8)		Retreading or modification of racing tyres is not permitted on vehicles faster than 12.50 (1/4 mile) / 8.00 (1/8 mile)	
Cars Faster than 12.00 (1/4) 7.70 (1/8)	Tyres	Cars with independent front suspension and cross-ply rear slicks are not permitted to use radial front tyres.	"Tyres" on page 231
Open cars Faster than 10.00 (1/4) 6.40 (1/8) or 140 mph		Radial front tyres are not allowed for use on RWD cars quicker than 10.00 (1/4 mile) / 6.40 (1/8 mile) or exceeding 140mph	



		Rollcage	
Unmodified cars slower than 11.00 (1/4) 7.00 (1/8)		No Roll bar required	
Open Comp cars slower 11.00 (1/4) 7.00 (1/8)	ıts	No Roll bar required	
Modified Cars Slower than 11.00 (1/4) 7.00 (1/8) fitted with 4 wheel disc brakes and airbags	Rollcage Requirements	No Roll bar required	"Roll Bars & Safety Cages" on page 219
Modified between 11.00- 11.99 (1/4) 7.00- 7.70 (1/8)		Single Rollover Hoop - Utilities may use 4 point cage design	
Unmodified between 10.00-10.99 (1/4) 6.40-7.00 (1/8)		Single Rollover Hoop - Utilities may use 4 point cage design	
Unmodified between 8.00-9.99 (1/4) 5.00-6.40 (1/8)	nts	6 Point full rollcage design required	
Street Open between 11.00-12.99 (1/4) 7.00-8.30 (1/8)	Rollcage Requireme	Single Rollover Hoop - Utilities may use 4 point cage design	"Roll Bars & Safety Cages" on page 219
Open street cars slower than 12.99 (1/4) 8.30 (1/8)	Re	No Roll bar required	
All other cars not listed faster than 11.00 (1/4) 7.00 (1/8)		6 Point full rollcage design required	



Driveline			
Cars Faster than 13.00 (1/4) 8.30 (1/8)	p Driveline	Where a cross member is not in the vicinity of the front universal joint, a tailshaft loop is required on supercharged street vehicles (turboed and nitrous and all rear wheel drive competition cars quicker than 13.00 (1/4 mile) / 8.30 (1/8 mile)	"Driveline Protection" on page 210
Cars Slower than 11.00 (1/4) 7.00 (1/8) fitted with 4 wheel disc brakes and airbags	Tailshaft Loop Driveline	No tailshaft loop required for vehicles fitted with 4 wheel disc brakes and airbags	"Driveline Protection" on page 210
Supercharged Faster than 11.00 (1/4) 7.00 (1/8)	Auto trans protection	Auto trans protection required	"Auto Trans Protection"
All cars faster than 10.00 (1/4) 6.40 (1/8)	Auto	Auto trans protection required	on page 209
All Cars Faster than 11.00 (1/4) 7.00 (1/8)	Flywheel Protection	Steel or Alloy flywheel required. No excessively machined units allowed.	#EL
All clutch cars Faster than 11.00 (1/4) 7.00 (1/8)	Bellhousing Protection	Cars faster than 11.00 (1/4 mile) / 7.00 (1/8 mile) require either aluminium bellhousing with a steel or titanium liner, or steel bellhousing or titanium bellhousing or shield.	"Flywheel Shields / Bellhousing" on page 211
All Cars with known performance faster than 7.50 (1/4) 4.90 (1/8)	Rear Axle	Full floating hubs required in certain classes	"Rear Axle" on page 213



Other Items			
Cars Faster than 11.00 (1/4) 7.00 (1/8)	Battery Location - OEM	Battery in OEM location	"Batteries" on page 209
Cars Faster than 12.00 (1/4) 7.70 (1/8)	Battery Location - Non OEM	Battery in non-OEM location and all competition cars require a battery isolation switch and labelled with a blue triangle	
All cars faster than 10.00 (1/4) 6.40 (1/8)	Racing Seat	A purpose built racing seat is required on all cars quicker than 10.00 (1/4 mile) / 6.40 (1/8 mile)	"Seats" on page 249
Cars Faster than 11.00 (1/4) 7.00 (1/8)	Window Net / Arm Restraints	Window net or Arm Restraints required	"Window Nets" on page 216
Cars Faster than 9.00 (1/4) 5.70 (1/8)	Fire Suppression System	Front engine Top Fuel dragsters, any supercharged vehicle with enclosed fibreglass or composite body running quicker than 9.00 (1/4 mile) / 5.70 (1/8 mile)	"Onboard Fire Suppression Systems" on page 239
Sedans Faster than 130 mph	Parachutes	Single parachute required for cars faster than 130mph that do not have 4 wheel braking	
Sedans Faster than 140 mph with 4 wheel braking	Parachutes	Single parachute required for cars faster than 140mph that <u>do</u> have 4 wheel braking	"Parachutes" on page 216
Sedans Faster than 200 mph	Parachutes	Twin parachutes required for all cars exceeding 200mph	
Supercharged Faster than 9.00 (1/4) 5.70 (1/8)	Liquid Overflow	Catch can required	"Liquid Overflow" on page 202
Supercharged Faster than 9.00 (1/4) 5.70 (1/8)	Lower Engine Containment Device	Require on supercharged, turboed or Nitrous injected vehicles faster than 9.00 (1/4 mile / 5.70 (1/8 mile)	"Lower Engine Containment Device" on page 203
Cars Faster than 11.00 (1/4) 7.00 (1/8)	Rootes Superchargers	6mm front endplate / 7.62mm rear endplate for Rootes blowers	"Superchargers" on page 204